

KD















SR户外投光灯



- 圆柱造型系列建筑照明投光灯
- 光源和驱动具备独立结构防水，高散热性压铸铝灯体，配高温钢化玻璃
- 低SDCM高亮度LED光源，高色温一致性
- 简单可靠的安装结构，方便各种作业环境下安装
- 配件丰富：支架表面安装，插泥安装











项目地址：南京
项目名称：万科·丝桥城
设计团队：上海·设计·照明设计

SR60												
	产品尺寸		电压		功率 (W)		光学角度		色温		流明输出	
	Ø60mm 103*95mm		DC24V/AC220		4		15 30 45		2700 3000 4000 5000 RGBW		0 300 0	
	Ø60mm 103*95mm		DC24V/AC220		6		15 30 45		2700 3000 4000 5000 RGBW		0 450 0	
SR80												
	产品尺寸		电压		功率 (W)		光学角度		色温		流明输出	
	Ø80mm 135*95mm		DC24V/AC220		6		15 30 45		2700 3000 4000 5000 RGBW		0 450 0	
	Ø80mm 135*95mm		DC24V/AC220		8		15 30 45		2700 3000 4000 5000 RGBW		0 600 0	
SR100												
	产品尺寸		电压		功率 (W)		光学角度		色温		流明输出	
	Ø100mm 155*105mm		DC24V/AC220		12		15 30 45		2700 3000 4000 5000 RGBW		0 900 0	
	Ø100mm 155*105mm		DC24V/AC220		15		15 30 45		2700 3000 4000 5000 RGBW		0 1125 0	
SR120												
	产品尺寸		电压		功率 (W)		光学角度		色温		流明输出	
	Ø120mm 180*120mm		DC24V/AC220		20		15 30 45		2700 3000 4000 5000 RGBW		0 1500 0	
	Ø120mm 180*120mm		DC24V/AC220		28		15 30 45		2700 3000 4000 5000 RGBW		0 2100 0	
SR120	Ø120mm 180*120mm		DC24V/AC220		36		15 30 45		2700 3000 4000 5000 RGBW		0 2700 0	

SRG60		 Max 12W IP65 表面安装 ON/OFF / DMX 																					
					产品尺寸	电压	功率 (W)	光学角度			色温			流明输出		可支持控制协议		CRI	防眩光	IP等级	可调角度		
					Ø60mm 103*95mm	DC24V/AC220	4	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	300	0	ON/OFF	-	DMX	90	是	IP65	是
					Ø60mm 103*95mm	DC24V/AC220	6	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	450	0	ON/OFF	-	DMX	90	是	IP65	是
Ø60mm 103*95mm	DC24V/AC220	8	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	600	0	ON/OFF	-	DMX	90	是	IP65	是					

SRG80		 Max 12W IP65 表面安装 ON/OFF / DMX 																					
					产品尺寸	电压	功率 (W)	光学角度			色温			流明输出		可支持控制协议		CRI	防眩光	IP等级	可调角度		
					Ø80mm 135*95mm	DC24V/AC220	6	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	450	0	ON/OFF	-	DMX	90	是	IP65	是
					Ø80mm 135*95mm	DC24V/AC220	8	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	600	0	ON/OFF	-	DMX	90	是	IP65	是
Ø80mm 135*95mm	DC24V/AC220	12	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	900	0	ON/OFF	-	DMX	90	是	IP65	是					

SRG100		 Max 20W IP65 表面安装 ON/OFF / DMX 																					
					产品尺寸	电压	功率 (W)	光学角度			色温			流明输出		可支持控制协议		CRI	防眩光	IP等级	可调角度		
					Ø100mm 155*105mm	DC24V/AC220	12	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	900	0	ON/OFF	-	DMX	90	是	IP65	是
					Ø100mm 155*105mm	DC24V/AC220	15	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	1125	0	ON/OFF	-	DMX	90	是	IP65	是
Ø100mm 155*105mm	DC24V/AC220	20	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	1500	0	ON/OFF	-	DMX	90	是	IP65	是					

SRG120		 Max 36W IP65 表面安装 ON/OFF / DMX 																					
					产品尺寸	电压	功率 (W)	光学角度			色温			流明输出		可支持控制协议		CRI	防眩光	IP等级	可调角度		
					Ø120mm 180*120mm	DC24V/AC220	20	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	1500	0	ON/OFF	-	DMX	90	是	IP65	是
					Ø120mm 180*120mm	DC24V/AC220	28	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	2100	0	ON/OFF	-	DMX	90	是	IP65	是
Ø120mm 180*120mm	DC24V/AC220	36	15	30	45	2700 3000 4000 5000	RGBW	可调色温	0	2700	0	ON/OFF	-	DMX	90	是	IP65	是					